

FORMING THE FUTURE



Überreicht durch

hieke

ingenieurbüro data gmbh

Aspastrasse 33
D-59394 NORDKIRCHEN
Tel. +49 (2596) 920-0
Fax +49 (2596) 920-92
eMail info@hieke.com
Web www.hieke.com

STANDARD TRANSFER PRESSES

标准多工位压力机

PRENSAS SCHULER S.A.

Av. Fagundes de Oliveira, 1515
09950-904 | Diadema, São Paulo | Brazil
Tel.: +55 11 4075 8444
vendas@schulergroup.com
www.schulergroup.com

SCHULER 
Member of the ANDRITZ GROUP

STANDARD TRANSFER PRESSES | 标准多工位压力机

Model 型号		TML4 800	TML4 1000	TML4 1200	TML4 1600	TML4 2000	TML4 2500	TML4 3200
Press force 冲压力		8,000 kN	10,000 kN	12,000 kN	16,000 kN	20,000 kN	25,000 kN	32,000 kN
Press force 冲压力		880 US tons	1,100 US tons	1,320 US tons	1,760 US tons	2,200 US tons	2,750 US tons	3,500 US tons
Bed length 台面长度		Bed width 台面宽度						
4,600 mm [181.1 in]	2,000 mm [78.74 in]	-	2,000 mm [78.74 in]	-	2,000 mm [78.74 in]	-	-	-
5,100 mm [200.78 in]	2,000 mm [78.74 in]	2,500 mm [98.42 in]	2,000 mm [78.74 in]	2,500 mm [98.42 in]	2,500 mm [98.42 in]	-	-	-
6,100 mm [240.15 in]	-	-	-	-	-	2,000 mm [78.74 in]	2,750 mm [108.26 in]	-
7,100 mm [279.52 in]	-	-	-	-	-	2,750 mm [108.26 in]	2,750 mm [108.26 in]	2,750 mm [108.26 in]
7,600 mm [299.21 in]	-	-	-	-	-	-	2,750 mm [108.26 in]	3,050 mm [120.07 in]
Drive 传动	Link 连杆式	Link 连杆式	Link 连杆式	Link 连杆式	Link 连杆式	Link 连杆式	Link 连杆式	Link 连杆式
Shut height 闭台高度	1,200 mm [47.24 in]	1,200 mm [47.24 in]	1,200 mm [47.24 in]	1,200 mm [47.24 in]	1,200 mm [47.24 in]	1,410 mm [55.51 in]	1,525 mm [60.04 in]	1,600 mm [62.99 in]
Slide stroke 滑块行程	610 mm [24.01 in]	762 mm [30 in]	762 mm [30 in]	762 mm [30 in]	762 mm [30 in]	900 mm [35.43 in]	914 mm [35.98 in]	914 mm [35.98 in]
Slide adjustment 滑块调节量	410 mm [16.14 in]	410 mm [16.14 in]	410 mm [16.14 in]	410 mm [16.14 in]	410 mm [16.14 in]	410 mm [16.14 in]	410 mm [16.14 in]	410 mm [16.14 in]
Stroke rate 冲次	10-30 rpm	10-30 rpm	10-30 rpm	10-30 rpm	10-30 rpm	10-28 rpm	8-25 rpm	8-25 rpm

* Metric dimensions are binding
* 结合公制尺寸